

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name:** ANTI-STATIC CLEANER

**Article number:** R265

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:** Tygris Industrial  
Unit 31  
Kyle Road Industrial Estate  
Irvine  
Ayshire  
KA12 8LE  
Tel +44 (0) 1294 311 066  
Fax +44 (0) 1294 277 115  
Email [technical@tygrisindustrial.com](mailto:technical@tygrisindustrial.com)

**Further information obtainable from:** Technical Department

**1.4 Emergency telephone number:** Tel +44 (0) 1294 311 066

## 2. Hazards identification

### 2.1. Classification of the substance or mixture

<b>Classification (EC 1272/2008)</b>	Physical and Chemical Hazards	Flam. Aerosol 1: H222;
	Human health	Eye Irrit. 2 - H319; STOT SE 3 - H336
	Environment	Not classified.

**Classification (1999/45/EEC)** Xi;R36. F+;R12. R67.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### 2.2. Label elements

**Label In Accordance With (EC) No. 1272/2008**



<b>Signal Word</b>	Danger
<b>Hazard Statements</b>	H222 Extremely flammable aerosol. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
<b>Precautionary Statements</b>	P102 Keep out of reach of children. P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P271 Use only outdoors or in a well-ventilated area. P261 Avoid breathing vapour/spray. P280 Wear protective gloves. P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+313 If eye irritation persists: Get medical advice/attention. P501 Dispose of contents/container in accordance with local regulations.
<b>Supplementary Precautionary Statements</b>	P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use. P280 Wear protective gloves/protective clothing/eye protection/face protection. P264 Wash contaminated skin thoroughly after handling. P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P312 Call a POISON CENTER or doctor/physician if you feel unwell. P313 Get medical advice/attention. P337 If eye irritation persists: P403+233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/container to ...

### 2.3. Other hazards

**PBT:**

### 3. Composition/information on ingredients

#### 3.2. Mixtures

AMMONIA ...%	< 1%
Index No.	REACH Registration No.
CAS-No.: 1336-21-6	EC No.: 215-647-6
Classification (EC 1272/2008)	Classification (67/548/EEC)
Skin Corr. 1B - H314	C;R34
STOT SE 3 - H335	N;R50
Aquatic Acute 1 - H400	
BUTANE	5-10%
Index No.	REACH Registration No.
CAS-No.: 106-97-8	EINECS: 203-448-7
Classification (EC 1272/2008)	Classification (67/548/EEC)
Flam. Gas 1 - H220	F+;R12
ISOBUTANE	1-5%
Index No.	REACH Registration No.
CAS-No.: 75-28-5	EINECS: 200-857-2
Classification (EC 1272/2008)	Classification (67/548/EEC)
Flam. Gas 1 - H220	F+;R12
PROPAN-2-OL	30-60%
Index No.	REACH Registration No.
CAS-No.: 67-63-0	EINECS: 200-661-7
Classification (EC 1272/2008)	Classification (67/548/EEC)
Flam. Liq. 2 - H225	F;R11
Eye Irrit. 2 - H319	Xi;R36
STOT SE 3 - H336	R67
PROPANE	10-30%
Index No.	REACH Registration No.
CAS-No.: 74-98-6	EINECS: 200-827-9
Classification (EC 1272/2008)	Classification (67/548/EEC)
Flam. Gas 1 - H220	F+;R12

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16

## 4. First aid measures

### 4.1. Description of first aid measures

<b>General information</b>	Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.
<b>Ingestion</b>	DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.
<b>Skin contact</b>	Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

## 5. Firefighting measures

### 5.1 Extinguishing Media

**Extinguishing media** Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards** Aerosol cans may explode in a fire.

### 5.3. Advice for firefighters

**Advice for fire-fighters** Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.2. Environmental precautions

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures** Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

### 6.4. Reference to other sections

## 7. Handling and storage

### 7.1 Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions** Must not be exposed to direct sunlight or temperatures above 50°C.

### 7.3. Specific end use(s)

## 8. Exposure controls/personal protection

### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min	
BUTANE	WEL	600 ppm	1450 mg/m <sup>3</sup>	750 ppm	1810 mg/m <sup>3</sup>
ISOBUTANE	WEL	800 ppm		800 ppm	
PROPAN-2-OL	WEL	400 ppm	999 mg/m <sup>3</sup>	500 ppm	1250 mg/m <sup>3</sup>
PROPANE		Asphyxiating	Asphyxiating	Asphyxiating	Asphyxiating

WEL = Workplace Exposure Limits

### 8.2. Exposure controls

#### Protective equipment



#### Engineering measures

Provide adequate general and local exhaust ventilation.

#### Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

#### Hand protection

Use protective gloves.

#### Eye protection

Use approved safety goggles or face shield.

#### Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

#### Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Aerosol
Colour	Typical
Odour	Characteristic odour
Flammability Limit - Lower(%)	0.8
Flammability Limit - Upper(%)	9.0

### 9.2. Other information

## 10. Stability and reactivity

### 10.1. Reactivity

### 10.2. Chemical stability

Stable under normal temperature conditions.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## 11. Toxicological information

### 11.1. Information on toxicological effects

Inhalation	May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. Irritating to respiratory system.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.
Skin contact	Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause sensitisation by skin contact. Irritating to skin.
Eye contact	Irritating to eyes. May cause chemical eye burns.
Route of entry	Inhalation. Skin and/or eye contact.

## 12. Ecological information

**Ecotoxicity** Dangerous for the environment if discharged into watercourses.

### 12.1. Toxicity

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## 13. Disposal considerations

**13.1. Waste treatment methods** Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

## 14. Transport information

### 14.1. UN number

UN No. (ADR/RID/ADN) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

### 14.2. UN proper shipping name

Proper Shipping Name AEROSOLS

### 14.3. Transport hazard class(es)

ADR/RID/ADN Class 2

ADR/RID/ADN Class Class 2: Gases

ADR Label No. 2.1

IMDG Class 2.1

ICAO Class/Division 2.1

### Transport Labels



### 14.4. Packing group

### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant No

### 14.6. Special precautions for user

EMS F-D, S-U

Tunnel Restriction Code (D)

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code



## 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>Uk Regulatory References</b>	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. The Control of Substances Hazardous to Health Regulations 2002.
<b>Statutory Instruments</b>	The Control of Substances Hazardous to Health Regulations 2002. The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.
<b>Approved Code Of Practice</b>	Classification and Labelling of Substances and Preparations Dangerous for Supply.
<b>Guidance Notes</b>	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

### 15.2. Chemical safety assessment

## 16. Other information

<b>Risk Phrases In Full</b>	R34 Causes burns. R12 Extremely flammable. R11 Highly flammable R36 Irritating to eyes. R37 Irritating to respiratory system. R67 Vapours may cause drowsiness and dizziness. R50 Very toxic to aquatic organisms.
<b>Hazard Statements In Full</b>	H319 Causes serious eye irritation. H314 Causes severe skin burns and eye damage. H222 Extremely flammable aerosol. H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H336 May cause drowsiness or dizziness. H335 May cause respiratory irritation. H400 Very toxic to aquatic life.

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.